

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
9 October 2003 (09.10.2003)


PCT

(10) International Publication Number
WO 03/082022 A1

- (51) International Patent Classification⁷: **A23G 9/12**
- (21) International Application Number: **PCT/US03/09125**
- (22) International Filing Date: **25 March 2003 (25.03.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:
60/367,532 25 March 2002 (25.03.2002) US
- (71) Applicant (for all designated States except US):
BUNN-O-MATIC CORPORATION [US/US]; 1400 Stevenson Drive, Springfield, IL 62703 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **KADYK, Jeffrey, W. [US/US]; 7535 Walnut Street, Peasant Plains, IL 62677 (US).**
- (74) Agents: **PETERS, Grant, H. et al.; Barnes & Thornburg, 2600 Chase Plaza, 10 S. LaSalle Street, Chicago, IL 60603 (US).**
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: REVERSING AUGER SYSTEM



(57) Abstract: A method and apparatus for producing a chilled or partially frozen beverage is provided. The system includes a beverage hopper (32) a chilling unit (44), a rotatable mixing member (38), a sensing member (230) for detecting an occurrence of a rotation reversal condition, a controller for generating a rotation reversal signal in response to the sensing member, and a drive motor (36) coupled to the mixing member for rotating the mixing member in a first direction and a second, reverse direction in response to a rotation reverse signal.